


CROWD CONTROL BARRIERS



1 METRE



2 METRES



PATENTED HANDLE



HOT-DIP GALVANISED FINISH



SEAMLESS, STRONG WELD



Advantages +



SEAMLESS, STRONG WELD

Strong welding to prevent cracks.



HOT-DIP GALVANISED FINISH (MINIMUM 80 MICRONS)

Highly corrosion-resistant treatment that prevents rust.



PATENTED HANDLE

Allows carrying two barriers at once (unique on the market).



COMPANY NAME OR LOGO

Laser cutting based on your logo.



REINFORCED INTERLOCKING SYSTEM



Extra-thick 5 mm connectors for strong and stable use.




MAXIMISE STORAGE SPACE

Can be easily stacked to free up storage space.



PRODUCTS	LENGTHS	OVERALL DIMENSIONS	SURFACE TREATMENT
	1000 mm (39") (6 inner rails)	Height: 1090 mm (43") Frame: Ø 32 mm (Ø 1.3")	Fully hot-dipped galvanised (after welding)
	2000 mm (79") (14 inner rails)	Inner rails: Ø 16 mm (Ø 0.6")	

BEST SELLERS



Headquarters: Hong Kong, China
Production & Operations Centre: Qingdao, China



contact@sinoconcept.com
www.sinoconcept.com