

CROWD CONTROL BARRIERS



1-METRE



2-METRE



PATENTED HANDLE



HOT-DIP GALVANISED FINISH



SEAMLESS, STRONG WELD



Advantages +



SEAMLESS, STRONG WELD

Strong welding to prevent cracks.



HOT-DIP GALVANISED FINISH (MINIMUM 80 MICRONS)

Highly corrosion-resistant treatment that prevents rust.



PATENTED HANDLE

Allows carrying two barriers at once (unique on the market).



COMPANY NAME OR LOGO

Laser cutting based on your logo.



REINFORCED INTERLOCKING SYSTEM



Extra-thick 5 mm connectors for strong and stable use.




MAXIMISE STORAGE SPACE

Can be easily stacked to free up storage space.



| PRODUCTS | LENGTHS | OVERALL DIMENSIONS | SURFACE TREATMENT |
|--|-----------------------------------|--|--|
|  | 1000 mm (39") (6 inner rails) | Height: 1090 mm (43") Frame: Ø32 mm (Ø1.3") | Fully hot-dipped galvanised (after welding) |
|  | 2000 mm (79") (14 inner rails) | Inner rails: Ø16 mm (Ø0.6") | |

BEST SELLERS



Headquarters: Hong Kong, China
Production & Operations Centre: Qingdao, China



contact@sinoconcept.com
<https://sinoconcept.com>