

# CROWD CONTROL BARRIERS



1-METRE



2-METRE



PATENTED HANDLE



HOT-DIP GALVANISED FINISH



SEAMLESS, STRONG WELD



# Advantages +



## SEAMLESS, STRONG WELD

Strong welding to prevent cracks.



## HOT-DIP GALVANISED FINISH (MINIMUM 80 MICRONS)

Highly corrosion-resistant treatment that prevents rust.



## PATENTED HANDLE

Allows carrying two barriers at once (unique on the market).



## COMPANY NAME OR LOGO

Laser cutting based on your logo.



## REINFORCED INTERLOCKING SYSTEM



Extra-thick 5 mm connectors for strong and stable use.




## MAXIMISE STORAGE SPACE

Can be easily stacked to free up storage space.



PRODUCTS	LENGTHS	OVERALL DIMENSIONS	SURFACE TREATMENT
	1000 mm (39") (6 inner rails)	Height: 1030 mm (40.6") Frame: Ø32 mm (Ø1.3")	Fully hot-dipped galvanised (after welding)
	2000 mm (79") (14 inner rails)	Inner rails: Ø16 mm (Ø0.6")	

## BEST SELLERS



Headquarters: Hong Kong, China  
Production & Operations Centre: Qingdao, China



contact@sinoconcept.com  
<https://sinoconcept.com>