



PLASTIC-RUBBER COMPOSITE WHEEL STOPS



550 MM (1.8')



900 MM (3')



1220 MM (4')




1650 MM (5.4')



1830 MM (6')



CONVENIENT STORAGE



HEAVY-DUTY STRUCTURE



REACH CERTIFIED



Headquarters: Hong Kong, China
Production & Operations Centre: Qingdao, China




contact@sinoconcept.com
<https://sinoconcept.com>

Advantages +




PLASTIC-RUBBER COMPOSITE

Cost effective, UV-resistant, and very sturdy.



HEAVY-DUTY STRUCTURE

Thick walls and V-shaped ribs for maximum strength in tough conditions.



REFLECTIVE FILMS

Embedded thermoplastic reflective road marking films to enhance visibility and safety.




CONVENIENT STORAGE

Screws, anchors, and caps stored underneath for easy setup.




CUSTOM-MADE PACKING

Designed for international shipping, easy storage and delivery.

PRODUCTS	TYPES	OVERALL DIMENSIONS (L*W*H)	MOUNTING HARDWARE
	550 mm (1.8')	550 x 150 x 100 mm (1.8' x 6" x 4")	 Coach screw: M12 x 160 mm (M12 x 6") Anchor: Ø17 x 105 mm (Ø0.67" x 4.1") Cap: Ø33.5 mm (Ø1.32")
	900 mm (3')	900x 150 x 100 mm (3' x 6" x 4")	
	1220 mm (4')	1220 x 150 x 100 mm (4' x 6" x 4")	
	1650 mm (5.4')	1650 x 150 x 100 mm (5.4' x 6" x 4")	
	1830 mm (6')	1830 x 150 x 100 mm (6' x 6" x 4")	

BEST SELLERS



Headquarters: Hong Kong, China
Production & Operations Centre: Qingdao, China



contact@sinoconcept.com
<https://sinoconcept.com>